

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
11 March 2004 (11.03.2004)

PCT

(10) International Publication Number
WO 2004/020096 A1

- (51) International Patent Classification⁷: B01L 3/02 [PL/PL]; ul. Raclawicka 4 m. 28, PL-02-739 Warszawa (PL).
- (21) International Application Number: PCT/PL2003/000023 (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: 17 March 2003 (17.03.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
P.355728 27 August 2002 (27.08.2002) PL
P.357148 15 November 2002 (15.11.2002) PL
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (71) Applicant (*for all designated States except US*): PZ HTL SPÓŁKA AKCYJNA [PL/PL]; ul. Daniszewska 4, PL 03-230 Warszawa (PL).
- (72) Inventors; and
- (75) Inventors/Applicants (*for US only*): CZERNECKI, Andrzej [PL/PL]; ul. Zakopianska 10, PL-03-934 Warszawa (PL). JANKOWSKI, Andrzej [PL/PL]; ul. Sucharskiego 4 m. 74, PL-01-390 Warszawa (PL). SARNA, Wojciech
- Published:
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: METHOD OF PIPETTE CALIBRATION

(57) Abstract: In the method of pipette calibration, the volume of liquid to be aspirated is manually set by turning in and out the adjustment screw regulating the length of the operational stroke of the plunger inside the shaft, the position of the adjustment screw is detected, and a signal corresponding to the position of the adjustment screw is sent to the pipette electronic system, and next the signal corresponding to the position of the adjustment screw is compared with values of points from the aspiration table or values of the aspiration function, which has been earlier input to the memory of the electronic system correspondingly as the standard aspiration table or aspiration function for the pipette, and next to the position of the adjustment screw, the value of the aspired liquid volume is assigned, and displayed on the display.

WO 2004/020096 A1

10/525236

DT01 Rec'd PCT/PTC 22 FEB 2005

1/PRTS

METHOD OF PIPETTE CALIBRATION

5

(Background of the Invention)**1. Field of the Invention**

10 This invention relates to the method of pipette calibration.

2. Description of the Related Art

15 The German patent No. 43 35 863 discloses a piston pipette comprising adjustment means to change the piston stroke, indicator means to indicate the dosed volume of liquid, and coupling elements placed between the adjustment means and indicator means, for changing the pipette correction coefficient determining the ratio of piston stroke to the indicated liquid volume. The pipette comprises switching device for disconnection of the coupling means and to change the pipette correction coefficient through re-adjustment of the adjustment means. The coupling means comprise two spur
20 gears connected with each other, whereas the adjustment means are joined with the adjustment spur gear rotated appropriately to the piston stroke, while indicator means are joined with the indicating spur gear rotated appropriately to the indicated liquid volume. One spur gear meshes with the adjustment spur gear, while the other spur gear meshes with the indicator spur gear, whereas the coupling spur gears are disposed on one axis, abut against a spring, and can be slid by the switching device along the axis in the
25 direction opposite to the spring action at de-coupling of at least one face coupling.

The U.S. patent No. 4,567,780 discloses a pipette having a body comprising manually actuated plunger assembly. The pipette includes electric contacts to detect the limit plunger position, linear position sensors generating an electric signal proportional to

the plunger distance from the limit position, and a converter converting these electric signals into indications of volume.

Further, the U.S. patent No. 5,389,341 discloses a pipette having a body with the lower and the upper end, wherein a cylinder open below the body lower end is disposed, and a piston is positioned inside the cylinder movable between the lower and the upper position to aspirate liquid into the pipette, and to dose liquid from the pipette. Known pipette moreover comprises a motor and a transmission to move the piston, an electronic control assembly to control the piston movements, a braking assembly to stop the piston movement in a pre-set position, a knob making a progressive-reciprocal and sliding movements inside the body, and the knob movement measurement assembly. The measurement assembly is connected with the control assembly in such a way, that sliding the knob generates signals for the control assembly powering the motor actuating the piston, so the piston movement is controlled by the elements of the control assembly.

The Polish patent No. 151372 describes an automatic microprocessor controlled pipette comprising a handle wherein a drive system is mounted consisting of a stepper motor, a feed screw, and a magnetic clutch, and screwable into the housing exchangeable shafts, each of which including a cylinder, a piston and a seal, and of an electronic system to count the electric pulses sent to the stepper motor, and the piston position detector placed on its path. In the handle a sleeve is disposed movably with respect to the handle, and rigidly connected with the stepper motor frame, the sleeve during mounting the shaft to the handle slides into an element, which upper portion is a cylinder slidably mating with the sleeve, while the lower portion is a cylinder wherein the piston is moving. Both cylinders of the element are co-axial, while the piston in its upper end is rigidly joined with a magnetic armature operating with cylindrically shaped magnetic clutch, which bases are the poles of the magnet. Each of the exchangeable shafts has coded information regarding its volume in the form of stripes contrasting with the shaft colour, or in the form of magnetic strips, while an optical or magnetic system is positioned in a recess in the controller housing to read this information.

Further, the Polish patent application No. P.325795 describes a calibration method for a pipette comprising a housing in the form of a handle, and a shaft with a plunger slid by a knob through an adjustment screw, wherein the volume of aspired liquid is set manually by turning the adjustment screw in and out to set the length of the operational stroke of the plunger in the shaft, the position of the adjustment screw is detected, and the signal corresponding to the position of the adjustment screw is sent to an electronic system, in which memory standard aspiration curves are previously stored in the form of a multinominal of n -th degree, and then the signal corresponding to the position of the adjustment screw is compared with one of the aspiration curves, and the position of the adjustment screw is assigned to the value of the aspired volume of liquid which is displayed on the display.

(Summary of the Invention)

According to the present invention, in the method of pipette calibration the volume of the aspired liquid is manually set by turning in and out the adjustment screw regulating the length of the operational stroke of the plunger in the shaft, the position of the adjustment screw is detected, and the signal corresponding to the position of the adjustment screw is sent to the electronic system of the pipette, where the signal corresponding to the position of the adjustment screw is compared with the values of the points from the aspiration table, which is previously input to the memory of the electronic system as the standard aspiration table for the pipette, and next to the position of the adjustment screw, the value of the aspired liquid volume is assigned, and displayed on the display.

Preferably the pipette liquid aspiration tables are assigned to various types of aspirated liquids.

Preferably the values of the aspiration table points depend on the factors influencing the value of the aspired volume of liquid.

Preferably the date of changing the values of the aspiration table points are entered to the electronic system memory and displayed on the display.

According to a variety of the present invention, in the method of pipette calibration the volume of the aspired liquid is manually set by turning in and out the adjustment screw regulating the length of the operational stroke of the plunger in the shaft, the position of the adjustment screw is detected, and the signal corresponding to the position of the adjustment screw is sent to the electronic system of the pipette, where the signal corresponding to the position of the adjustment screw is compared with the values of the points from the aspiration function, which is previously input to the memory of the electronic system as the standard aspiration function for the pipette, and next to the position of the adjustment screw, the value of the aspired liquid volume is assigned, and displayed on the display.

Preferably the pipette liquid aspiration functions are assigned to various types of aspirated liquids.

Preferably the values of the aspiration functions depend on the factors influencing the value of the aspired volume of liquid.

Preferably the date of changing the values of the aspiration functions are entered to the electronic system memory and displayed on the display.

According to another variety of the present invention, in the method of pipette calibration the volume of the aspired liquid is manually set by turning in and out the adjustment screw regulating the length of the operational stroke of the plunger in the shaft, the position of the adjustment screw is detected, and the signal corresponding to the position of the adjustment screw is sent to the electronic system, to the memory of which the standard aspiration curves for the pipette are earlier input, and the signal corresponding to the position of the adjustment screw is compared with one of the aspiration curves, where the signal corresponding to the position of the adjustment screw is converted into the displayed digital value simultaneously with determination of the selected position from the whole range of the adjustment screw positions related to the display of this digital value.

Preferably in the read-out field for the set volume a marker is applied, indicating the direction of adjustment screw position changes in order to reach the selected position by the adjustment.

The advantage of the methods according to the invention is the ease of pipette calibration for various types of liquid and aspiration conditions, and various types of applied tips, with reference to the pipette aspiration table or pipette aspiration function earlier input into the memory of the pipette electronic system, and possibly modified. Moreover the solution according to the invention enhances the accuracy of the set volume for required value displayed on the display, and repeatability of results.

(Brief description of the drawings)

The accompanying drawings, which are incorporated in, and form a part of the specification, illustrate embodiments of the present invention and, together with the description, serve to explain the principles of the invention. In the drawings:

Fig. 1 shows longitudinal section of the pipette;

Fig. 2 shows front view of the pipette.

(Detailed description of the Invention)

Reference will now be made in detail to the preferred embodiments of the invention, examples of which are illustrated in the accompanying drawings.

The pipette comprising a handle (1) and shaft (2) is assigned for aspirating fluid into a disposable tip (3). A plunger (4) sealed by the means of a seal (5) moves inside the shaft (2). The plunger (4), which is driven by a rod (6) pressed by the button (7) makes reciprocal movements. When the plunger (4) moves upwards, liquid is aspirated to the tip (3), and while the plunger (4) moves downwards, liquid is dispensed from the tip (3). The movements of the rod (6) are limited by two stops, i. e. the upper stop (8) limiting the move upwards, and the lower stop (9) limiting the move downwards. Hence the upper

stop (8) constitutes the restriction for the rod (6) in its motion upwards, and the lower stop (9) constitutes the restriction for the button (7) in its motion downwards. The position of the upper stop (8) is adjustable, whereas the adjustment screw (10) is assigned for altering its position. The adjustment screw (10) is turned in or out of the nut (11) which is an element of the handle (1), by the use of the knob (12). Turning the knob (12) causes rotation of the leading sleeve (13). In the hole of the leading sleeve (13) grooves (14) are made, wherein longitudinal cogs (15) disposed on the adjustment screw (10) move during turning the adjustment screw (10) in and out. Change of position of the upper stop (8), which is an element of the adjustment screw (10), results in decreasing or increasing the operational stroke of the plunger (4), hence in the increase or decrease of the volume of liquid aspirated into the pipette. The rod (6) is pressed to the upper stop (8) by the return spring (16) which simultaneously causes the return of the plunger (4) to its upper position. In turn, the lower stop (9) is pressed to the knob (12) by the blow-out spring (17).

Aspiration of liquid requires pressing of the button (7) until it abuts against the lower stop (9), insertion of the tip into the liquid being aspirated, and releasing the button (7) until the rod (6) abuts against the upper stop (8). A movement on the sector (L_1) will be made. Liquid dispensing requires again re-pressing of the button (7) to the lower stop (9). Again a movement on the sector (L_1) will be made. In order to remove the remainings of the liquid from the tip (3) the lower stop (9) must be pressed by the button (7), overcome the resistance of the blow-out spring (17), and press the button (7) to the knob (12). A movement on the sector (L_2) will be made.

The position of the adjustment screw (10) is monitored by the optical system (18) of the encoder dial (19). The encoder dial (19) is fixed to the leading sleeve (13) and turns simultaneously with the knob (12) and the sleeve (13). The optical system (18) monitors the movements of the encoder dial (19), thanks to what the current position of the adjustment screw (10) and the upper stop (8) is detected. Current position of the adjustment screw (10) in the form of an information on the number of pulses counted by the optical system (18) is transferred to the electronic system (20). The electronic system

(20) compares the signal corresponding to the position of the adjustment screw (10) with the values of the points from the standard aspiration table, which in the form of the standard aspiration table has been earlier input to its memory, assigns to the position of the adjustment screw (10) the value of the liquid being aspirated, and displays it on the display (21). The electronic system (20) automatically selects previously entered into its memory values of the points of the aspiration table with respect to the type of the shaft (2) mounted to the pipette. The signal regarding the type of the shaft (2) is transmitted to the electronic system (20) by the sensors (22).

In case of aspirating liquid of properties other than water, for which a standard aspiration table was input to the memory of the electronic system (20), actual volumes of liquid aspired by the pipette must be determined, and next, by pressing the button (23) and rotating the knob (12), new values must be input to the aspiration table in the electronic system (20), monitoring their appearance on the display (21). After double pressing the button (23) and confirming the new values entered to the memory, the electronic system (20) automatically performs the calibration of the pipette.

In similar way the calibration of the pipette is accomplished in case of change of factors influencing the aspirated amount of liquid, such as type of the tip (3), atmospheric pressure, air humidity, liquid temperature and ambient temperature. Moreover in the memory of the electronic system (20) it is possible to store the date of changing the values of points in the aspiration table, and then display it on the display (21).

The electronic system (20) is powered from a battery (24).

In a variety of the pipette calibration method according to the invention, the electronic system (20) compares the signal corresponding to the position of the adjustment screw (10) with the values of the aspiration function, which in the form of the standard aspiration function has been earlier input to its memory. In this case it is also possible to assign various aspiration functions to various types of aspirated liquids, to relate the aspiration function values to factors influencing the value of the aspired volume of liquid, and to input the date of introducing changes to the values of the aspiration function to the memory of the electronic system (20) and display it on the display (21).

In yet another variety of the pipette calibration method according to the invention, which may constitute a development of the calibration methods described above, the volume of the liquid being aspirated is set in the pipette manually by turning in and out the adjustment screw (10) regulating the length of the operational stroke of the plunger (4) in the shaft (2). Next, after determination of the position of the adjustment screw (10), an electric signal in the form of electric pulses corresponding to the position of the adjustment screw (10) is sent to the electronic system (20), to which memory earlier standard aspiration curves have been input preferably in the form of a multinomial of n -th degree, and the signal corresponding to the adjustment screw (10) position is compared to one of the aspiration curves. In case when to the same value displayed on the display (21) correspond few electric pulses sent to the electronic system (20), the electronic pulses defining the position of the adjustment screw (10) are converted in the electronic system (20) into digital value displayed of the display (21). The conversion occurs simultaneously with determination of the selected position from the whole range of the adjustment screw (10) positions related to the display of this digital value.

The read-out of the set liquid volume value on the display (21) of the pipette depends on the number of electric pulses counted in the electronic system (20), taking into account the correction for calibration. This correction takes into account, according to the invention, the type of the shaft (2) applied in the pipette, and the distance of intersection of the aspiration curve with the axis of pulses. Moreover, a correction for the determined range of pulses is taken into account in read-out, when the whole range of the pipette aspiration capability is divided into sub-ranges, and it is possible to introduce an individual correction for each range of the counted pulses. It is also possible to introduce additional corrections resulting from temporary calibration. This way the calculated volume corresponds to the displayed value, since there is unique assignment of the given value to the selected pulse from the range of this value.

According to the invention, in the read-out field for the set volume a marker is applied, indicating the direction of adjustment screw (10) position changes in order to reach the selected position by the adjustment screw. Denotation of values is accomplished

by blinking of the last digits in case of displaying a value, which is not denoted, and lack of blinking for denoted values. Markers for increase and decrease may be displayed after the last digit of the symbol at the top of the digit for increase, and at the bottom of the digit for decrease.

5

10

15

20

25

5 **We claim:**

1. The method of pipette calibration, the pipette comprising a body in the form of a handle and a shaft, wherein a plunger slid by a knob through an adjustment screw is placed, wherein the volume of the aspired liquid is manually set by turning in and out the adjustment screw regulating the length of the operational stroke of the plunger in the shaft, the position of the adjustment screw is detected, and the signal corresponding to the position of the adjustment screw is sent to the electronic system of the pipette characterised by that the signal corresponding to the position of the adjustment screw is compared with the values of the points from the aspiration table, which is previously input to the memory of the electronic system as the standard aspiration table for the pipette, and next to the position of the adjustment screw, the value of the aspired liquid volume is assigned, and displayed on the display.

2. The method according to the claim 1 characterised by that the pipette liquid aspiration tables are assigned to various types of aspirated liquids.

3. The method according to the claim 1 characterised by that the values of the aspiration table points depend on the factors influencing the value of the aspired volume of liquid.

4. The method according to the claim 1 characterised by that the date of changing the values of the aspiration table points are entered to the electronic system memory and displayed on the display.

5. The method of pipette calibration, the pipette comprising a body in the form of a handle and a shaft, wherein a plunger slid by a knob through an adjustment screw is placed, wherein the volume of the aspired liquid is manually set by turning in and out the

adjustment screw regulating the length of the operational stroke of the plunger in the shaft, the position of the adjustment screw is detected, and the signal corresponding to the position of the adjustment screw is sent to the electronic system of the pipette characterised by that the signal corresponding to the position of the adjustment screw is compared with the values of the points from the aspiration function, which is previously input to the memory of the electronic system as the standard aspiration function for the pipette, and next to the position of the adjustment screw, the value of the aspired liquid volume is assigned, and displayed on the display.

6. The method according to the claim 5 characterised by that the pipette liquid aspiration functions are assigned to various types of aspirated liquids.

7. The method according to the claim 5 characterised by that the values of the aspiration functions depend on the factors influencing the value of the aspired volume of liquid.

8. The method according to the claim 5 characterised by that the date of changing the values of the aspiration functions are entered to the electronic system memory and displayed on the display.

9. The method of pipette calibration, the pipette comprising a body in the form of a handle and a shaft, wherein a plunger slid by a knob through an adjustment screw is placed, wherein the volume of the aspired liquid is manually set by turning in and out the adjustment screw regulating the length of the operational stroke of the plunger in the shaft, the position of the adjustment screw is detected, and the signal corresponding to the position of the adjustment screw is sent to the electronic system, to the memory of which the standard aspiration curves for the pipette are earlier input, and the signal corresponding to the position of the adjustment screw is compared with one of the aspiration curves, characterised by that the signal corresponding to the position of the adjustment screw is converted into the displayed digital value simultaneously with determination of the selected position from the whole range of the adjustment screw positions related to the display of this digital value.

12

10. The method according to the claim 9 characterised by that in the read-out field for the set volume a marker is applied, indicating the direction of adjustment screw position changes in order to reach the selected position by the adjustment.

5

10

15

20

25

10/525236




Fig. 1

Fig. 2

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/PL 03/00023

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B01L3/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 B01L G01N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 998 218 A (CONLEY PAUL G ET AL) 7 December 1999 (1999-12-07) column 2, line 50 -column 3, line 40 column 11, line 39 -column 12, line 16 abstract; figure 11 ----	1-10
X	PL 325 795 A (P Z HTL SA) 25 October 1999 (1999-10-25) cited in the application the whole document ----	1-10
A	EP 0 070 571 A (SCIENT MFG IND) 26 January 1983 (1983-01-26) page 12, line 15 -page 13, line 15; figures ----- -/--	1,3,5,7, 9,10

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the International filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the International filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *G* document member of the same patent family

Date of the actual completion of the International search

8 July 2003

Date of mailing of the International search report

24/09/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Smith-Hewitt, L

Form PCT/ISA/210 (second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

International Application No

PCT/PL 03/00023

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	FR 2 807 558 A (GILSON SA) 12 October 2001 (2001-10-12) page 17, line 1 -page 17, line 32; figures ---	1-10
A	US 4 905 526 A (MAGNUSSEN JR HAAKON T ET AL) 6 March 1990 (1990-03-06) column 15, line 64 -column 17, line 11; figure 5A ---	1-10
A	EP 0 864 364 A (BECTON DICKINSON CO) 16 September 1998 (1998-09-16) column 10, line 56 -column 11, line 42; figures -----	1-10

Form PCT/ISA/210 (continuation of second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/PL 03/00023

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5998218	A	07-12-1999	AU 733643 B2	17-05-2001
			AU 4259597 A	26-03-1998
			EP 0923720 A1	23-06-1999
			WO 9810265 A1	12-03-1998
PL 325795	A	25-10-1999	PL 325795 A1	25-10-1999
EP 0070571	A	26-01-1983	US 4475666 A	09-10-1984
			US 4528161 A	09-07-1985
			EP 0070571 A2	26-01-1983
			JP 58050465 A	24-03-1983
			US 4476999 A	16-10-1984
FR 2807558	A	12-10-2001	FR 2807558 A1	12-10-2001
			AU 4849901 A	23-10-2001
			WO 0176749 A1	18-10-2001
US 4905526	A	06-03-1990	US 4671123 A	09-06-1987
			US 5187990 A	23-02-1993
			AU 589891 B2	26-10-1989
			AU 3890685 A	22-08-1985
			CA 1293709 C	31-12-1991
			DE 3586289 D1	13-08-1992
			DE 3586289 T2	13-06-1996
			DE 3588071 D1	25-01-1996
			DE 3588071 T2	13-06-1996
			EP 0152120 A2	21-08-1985
			EP 0428500 A2	22-05-1991
			FR 2559904 A1	23-08-1985
			JP 1807271 C	10-12-1993
			JP 5013709 B	23-02-1993
			JP 60193549 A	02-10-1985
EP 0864364	A	16-09-1998	US 6090348 A	18-07-2000
			EP 0864364 A2	16-09-1998
			JP 10311781 A	24-11-1998

Form PCT/ISA/210 (patent family annex) (July 1992)